



Not every project can accommodate a standard sized hot water cylinder which is why we specialise in manufacturing bespoke hot water storage solutions to meet your exact specifications.

Depending on the capacity required and height available, our flexible manufacturing process can deliver the slimmest hot water cylinders on the market.

So we have prepared this quick ready reckoner showing the various shell sizes which can be used to deliver the required capacity.

Approx. Capacity	SHELL DIAMETER							
	280mm	300mm	350mm	375mm	400mm	450mm	500mm	600mm
40L	720	645	480	415	375	-	-	-
50L	900	800	600	515	470	400	-	-
75L	1350	1200	900	775	700	600	-	-
85L	1515	1345	1000	900	800	675	-	-
95L	1730	1535	1150	995	900	750	600	-
105L	1910	1700	1270	1100	1000	825	670	-
115L	2050	1825	1370	1180	1050	890	720	-
120L	2100	1875	1400	1210	1075	900	750	-
135L	-	2145	1600	1400	1200	1030	850	-
140L	-	2240	1675	1450	1250	1050	900	-
150L	-	-	1800	1550	1350	1125	950	-
165L	-	-	1975	1700	1475	1200	1050	-
180L	-	-	2155	1860	1600	1300	1150	770
190L	-	-	2275	1965	1700	1380	1200	815
210L	-	-	-	2170	1850	1500	1300	880
250L	-	-	-	-	2200	1800	1500	1050
280L	-	-	-	-	-	2040	1700	1200
300L	-	-	-	-	-	2150	1800	1300
360L	-	-	-	-	-	-	2200	1500
440L	-	-	-	-	-	-	-	1800

For 35mm foam lagging add 70mm to the diameter and 35mm to the height

For 50mm foam lagging add 100mm to the diameter and 50mm to the height

For 100mm foam lagging add 200mm to the diameter and 100mm to the height

Additional lagging options available to suit your requirements – contact us to find out more

POWER FLOW

THERM FLOW

ELECTRAFLOW

VENTED